



This MSA Compliant SFP transceiver provides 100Base-FX throughput up to 100m over a fiber connection using an LC connector. 100Base-FX Fiber SFP works at 850nm wavelength and 550 meters high.

MSA and TAA Compliant 100Base-FX Fiber SFP Transceiver.



**Fiber SFP Module
100BASE-FX Fiber SFP**

TECHNICAL SPECS

Product Type
SFP (mini-GBIC)

Ethernet Technology
Gigabit Ethernet

Interfaces/Ports Details
1 x 100Base-FX Fiber SFP

Media Type Supported
Optical Fiber

Network Technology
100Base-FX Fiber SFP

Application/Usage
Data Networking

Temperature
Operating: -40°C to +85°C

Compatibility
MSA, TAA

It is also capable of withstanding rugged environments and can operate at temperatures between -40°C to +85°C. It is built to MSA standards and is uniquely serialized and data-traffic and application tested to ensure that they will integrate into your network seamlessly. It is built to meet or exceed the specifications of MSA Compliant, as well as to comply with MSA (Multi-Source Agreement) standards to ensure seamless network integration. All of our transceivers are Trade Agreements Act (TAA) compliant.

Part Number G0900249 **Part Description** 100Base-FX Fiber SFP Transceiver

Ordering Information **CALL: (866) 652-3500**

Email: sales@clearcube.com to order or for more information

