



Universal Compatibility for High Security Applications That Demand Isolation Between Networks
Connects multiple peripherals while maintaining air-gap isolation and preventing signal leakage.



4 Port Universal Switch

KEY FEATURES

Number of Computers

4

Number of Displays

2

Max Resolutions Support

3840 x 2160 pixels (UHD 4K) @ 60Hz (DP Input/HDMI 2.0 Output only)

3840 x 2160 pixels (UHD 4K) @ 30Hz (DP)

Console Ports (Devices)

Console Mouse and Keyboard Ports: USB Type-A female connector (1 designated port for mouse and 1 designated port for keyboard)

Console Display Ports: 2 x DP 1.2a or 2 x HDMI 2.0 via combo connector

Console Audio Jack: 1/8" (3.5mm) female

Console CAC Input when equipped with a CAC port: USB Type A

DCU Port: RJ25

Computer Ports

Computer Display Ports: 2 x DP 1.2a port or 2 x HDMI 2.0 via combo connector

Computer Audio Jack: 1/8" (3.5mm) female

Computer Keyboard/Mouse Ports: USB Type B

Computer CAC Ports when equipped with a CAC port: USB Type B

TECHNICAL SPECS

Weight

4.85 lbs.(2.2 kg.)

Temperature

Office/Operating: 32° to 104° F (0° to 40° C)

Storage: -4° to 140° F (-20° to 60° C)

Humidity: 0% - 80% RH, non-condensing

Dimensions

12.5 (W) x 3.6 (H) x 6.2 (L) inches

Power

12V 1.5A DC Power Supply

AC Input

100 to 240VAC

Physical Characteristics

Heavy-duty aluminum enclosure with metal faceplate

Security

Certified to NIAP Protection Profile PSS Ver 3.0, which exceeds EAL4. NIAP listed.

Compliance

FCC Class A, UL, CE, RoHS, ICES, RCM

IDEAL FOR:

- State & Local Government
- Department of Defense
- Military
- Command & Control Centers

Part Number	Part Description
G0900426	KVM 4-Port, 2 Head Universal DP/HDMI

BENEFITS



Certified for NIAP Protection Profile PSS 3.0.



Support DisplayPort, HDMI, and DVI-D via Passive Cabling



Integrated anti-tamper switch



Rear View

INNOVATIVE SECURITY

Integrated anti-tamper switches immediately render the unit permanently inoperable in the event of a breach attempt. Unique mechanical design accommodates desktop or under-desk mounting with optional bracket along with an optional remote-control capability to further declutter the operator's desk. Innovative channel designator inserts and no keyboard shortcuts for switching ensure operators are always aware of which security enclave they are working on.

FUTURE PROOF

Utilizing an innovative display connection technology, the Belkin NIAP PP3.0 certified Secure Universal KVM Switch can simultaneously accommodate legacy DVI-D input/output as well as modern, high resolution HDMI and DisplayPort input/outputs using passive cabling. The innovative connector design and internal video conversion allows the same SKVM to be used for legacy systems and accommodate anticipated technology changes over time, ensuring today's investment is not rendered obsolete as underlying systems get upgraded.

PLUG AND PLAY

The Belkin Secure Universal KVM is the ideal solution for systems using high performance Display Port graphics outputs as well as monitor inputs. The platform is fully compatible with Display Port connections supporting resolutions of UHD 4K @60Hz. The platform's flexibility also allows support for standard definition and HD resolutions supported by DVI-D Single Link without the need for external graphic conversions using costly active cables. The platform is truly plug and play now and into the future.

Ordering Information CALL: (866) 652-3500

Email: sales@clearcube.com to order or for more information



Supply Chain & Manufacturing



Command & Control Centers



Government Agencies



Financial Services



Training & Education



Healthcare & Medical Technology



Engineering & Design



Department of Defense



Digital Signage



Oil & Gas



Small & Medium Business



Media & Entertainment