



**Zero Client CD9522**

Budget friendly zero client for virtual desktop infrastructure and remote computing  
**No special OS drivers, no moving parts that fail, with 2 standard DVI ports.**

**KEY FEATURES**

**Chipset**  
Teradici TERA2321 PCoIP

**Video**  
Single: 2560x1600  
Dual: 1920x1080

**External Ports**  
2 x DVI-D  
Mic+Speaker 3.5mm  
4 x USB 2.0  
1 x 1Gbps RJ45

**Memory**  
512MB

**Storage**  
256Mbit

**TECHNICAL SPECS**

**Weight**  
1 lbs.

**Dimensions**  
1.8" (H) x 5.9" (W) x 5.1" (D)

**Environment**  
*Storage Temperature:* -20°C to 70°C (-4°F to 140°F)  
*Operating Temperature:* 0°C to 40°C (32F to 104°F)

**Power**  
Universal 100-240 VAC, 50-60Hz  
Output: 12V DC, 3A

**Physical Characteristics**  
Plastic

**Security**  
Kensington Slot for use with Kensington locks  
Integrated PKI approved smart card reader on CD7034

**IDEAL FOR:**

- State & Local Government
- IT Professionals
- Military & Defense
- Command & Control Centers
- Healthcare, Financial, & Insurance
- Call Centers
- Oil & Gas

**Part Number    Part Description**

**G0900251 - CD9922**

**BENEFITS**



Delivers full desktop computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and in a small space



No open storage, only firmware configuration



Supports remote workstation cards, and HP Anyware, and VMware PCoIP



Fully TAA compliant


**Rear View**

### WORKS WITH EXISTING NETWORKS

CD9522 Zero Clients work with existing Ethernet networks and have two standard DVI ports (no display port converter cable needed).

### OPTIMAL QUALITY

CD9522 Zero Clients deliver simultaneous full-screen, full-motion video at high resolution. Users can configure a different resolution and orientation (landscape or portrait) for each monitor. Supported resolutions include one display at 2560x1600 or two displays at 1920x1200.

### SIMPLE INSTALLATION & SECURE HARDWARE

ClearCube delivers high performance and robust security in a new PCoIP TERA2 computing solution unhindered by distance. With dual monitors and full-performance video, CD9522 connects to VMware virtual desktops on SmartVDI systems, 3rd-party virtual machines, and remote ClearCube Blade PCs.

In ClearCube Centralized and Virtualized Desktop Infrastructures (CVDI), VMware Horizon can broker connections from CD9522 zero clients to both SmartVDI and Blade PC resources. Dedicated 1:1 users can take advantage of hardware accelerated PCoIP chips in ClearCube Blade PCs to support legacy, mission-critical, and/or GPU-intensive applications.

The CD9522 TERA2321 chip supports AES-128/AES-256 Suite B Ciphers, USB 2.0 devices, and full power management with Wake-on-LAN support.

### HIGH PERFORMANCE, OPTIMAL QUALITY

CD9522 Zero Client requires no special OS drivers. There are no moving parts that can fail and no removable parts that encourage user tampering or theft. The units easily connect all standard peripherals including multiple monitors, keyboard, mouse, audio input/output devices and USB peripherals. Advance configuration options allow management of USB devices including enabling/disabling entire classes of mass storage devices.

**Ordering Information: CALL 512.652.3500**

Email: [sales@clearcube.com](mailto:sales@clearcube.com) to order or for more information



Supply Chain & Manufacturing



Command & Control Centers



Government Agencies



Financial Services



Training & Education



Healthcare & Medical Technology



Engineering & Design



Department of Defense



Digital Signage



Oil & Gas



Small & Medium Business



Media & Entertainment