



Zero Client CD7522P



Budget Friendly Dual Fiber Zero Client
Great for Centralized and Virtualized Desktop Infrastructure

KEY FEATURES

Chipset

Teradici TERA2321 PCoIP

Video

Single: 2560x1600

Dual: 1920x1080

External Ports

2 x DVI

Mic+Speaker 3.5mm

4 x USB 2.0

1 x SFP-Fiber/Copper 1Gbps

Memory

512MB

Storage

256Mbit

TECHNICAL SPECS

Weight

1.75 lbs.

Dimensions

1.8" (H) x 5.9" (W) x 5.1" (D)

Environment

Storage Temperature: -20°C to 70°C (-4°F to 140°F)

Operating Temperature: 0°C to 40°C (32°F to 104°F)

Power

Universal 100-240 VAC, 50-60Hz

Output: 12V DC, 3A

Physical Characteristics

Plastic

Security

Kensington Slot for use with Kensington locks
Integrated PKI approved smart card reader on CD7034

IDEAL FOR:

- State & Local Government
- IT Professionals
- Military & Defense
- Command & Control Centers
- Healthcare, Financial, & Insurance
- Call Centers
- Oil & Gas

Part Number Part Description

G0900261 - CD7522P

BENEFITS



Delivers full desktop computing experience via an IP connection to Blade PCs or VMware Horizon desktop with no noise, less heat, and in a small space



No open storage, only firmware configuration



Supports remote workstation cards, and HP Anyware, and VMware PCoIP



Fully TAA compliant

**Rear View**

SIMPLE AND SECURE

CD7522 Zero Client requires no special OS drivers. There are no moving parts that can fail and no removable parts that encourage user tampering/theft. The units easily connect all standard peripherals including multiple monitors, keyboard, mouse, audio input/output devices and USB peripherals. Advanced configuration options allow specific policy-based management of USB devices including enabling/disabling entire classes of mass storage devices.

DUAL FIBER ZERO CLIENT

ClearCube delivers high performance and robust security in a new PCoIP TERA2 computing solution unhindered by distance. With dual-monitors and full performance video, CD7522 connects to VMware virtual desktops on SmartVDI systems, 3rd party virtual machines, and remote ClearCube Blade PCs.

In ClearCube Centralized and Virtualized Desktop Infrastructures (CVDI), CD7522 can broker a connection to both SmartVDI and Blade PC resources using VMware Horizon. Dedicated 1:1 users can take advantage of hardware accelerated PCoIP chips in ClearCube's Blade PCs to support legacy, mission-critical, and/or GPU-intensive applications. CD7522 Zero Client's SFPs support 100 Base and 1000 Base connections to host resources.

AES-256 Suite B Ciphers, USB 2.0 devices, and full power management with Wake-on-LAN support are supported by CD7522's TERA2321 chip.

HIGH PERFORMANCE, OPTIMAL QUALITY

CD7522 Zero Clients deliver simultaneous full screen, full motion video at high resolution on one or two monitors. Each monitor is independently configurable for both resolution and choice of portrait or landscape orientation. Supported resolutions are 2 x 2560x1600 or 4 x 1920x1200.

Ordering Information: CALL 512.652.3500

Email: sales@clearcube.com to order or for more information



Supply Chain & Manufacturing



Command & Control Centers



Government Agencies



Financial Services



Training & Education



Healthcare & Medical Technology



Engineering & Design



Department of Defense



Digital Signage



Oil & Gas



Small & Medium Business



Media & Entertainment